

Best Security SYSTEM SERVICE



2MP IR Indoor Dome



HIP-HD230IR

- Sony Exmor 2.1MP Image Sensor
- Fixed Lens 3.6mm
- 30m IR distance
- Max 25/30fps@all resolution
- Support PoE/Onvif

2MP IR Indoor Dome



HIP-HD230VIR

- Sony Exmor 2.1MP Image Sensor
- Motorized 2.8~12mm VF Mega Lens
- 30m IR distance
- Max 25/30fps@all resolution
- Support PoE/Onvif

2MP Bullet



HIP-HP235IR

- Sony Exmor 2.1MP Image Sensor
- Fixed Lens 3.6mm
- 35m IR distance
- Max 25/30fps@all resolution
- Support PoE/Onvif
- IP68 Waterproof

2MP Bullet



HIP-HP260IR

- Sony Exmor 2.1MP Image Sensor
- Fixed Lens 6mm
- 60m IR distance
- Max 25/30fps@all resolution
- Support PoE/Onvif
- IP68 Waterproof

2MP Bullet



HIP-HP242VIR

- Sony Exmor 2.1MP Image Sensor
- Motorized 2.8~12mm VF Mega Lens
- 40m IR distance
- Max 25/30fps@all resolution
- Support PoE/Onvif
- IP68 Waterproof

2MP Bullet



HIP-HP260EVIR

- Sony Exmor 2.1MP Image Sensor
- Motorized 2.8~12mm VF Mega Lens
- 60m IR distance
- Max 25/30fps@all resolution
- Support PoE/Onvif
- IP68 Waterproof

2MP IR Outdoor Vandal Dome



HIP-HV2VIR

- Sony Exmor 2.1MP Image Sensor
- Motorized 2.8~12mm VF Mega Lens
- 30m IR distance
- Max 25/30fps@all resolution
- Support PoE/Onvif
- IP66 Waterproof

3MP IR Indoor Dome



HIP-HD330VIR

- Sony Exmor 3.14MP Image Sensor
- Motorized 2.8~12mm VF Mega Lens
- 30m IR distance
- Max 20fps@all resolution
- Support PoE/Onvif

3MP Bullet



HIP-HP342VIR

- Sony Exmor 3.14MP Image Sensor
- Motorized 2.8~12mm VF Mega Lens
- 40m IR distance
- Max 20fps@all resolution
- Support PoE/Onvif
- IP68 Waterproof

3MP Bullet



HIP-HP360EVIR

- Sony Exmor 3.14MP Image Sensor
- Motorized 2.8~12mm VF Mega Lens
- 60m IR distance
- Max 20fps@all resolution
- Support PoE/Onvif
- IP68 Waterproof

3MP IR Outdoor Vandal Dome



HIP-HV330VIR

- Sony Exmor 3.14MP Image Sensor
- Motorized 2.8~12mm VF Mega Lens
- 30m IR distance
- Max 20fps@all resolution
- Support PoE/Onvif
- IP66 Waterproof

NVR



HVR-SN30 Series

- Plug&Play Embedded NVR
- Up to 8ch HD IP Cameras Real-time
- PoE Switching HUB Built-in(Up to 8ch)
- Auto IP Camera Detection
- Support Onvif

IR Indoor Dome



STD-A2M24IR

- Sony Exmor 2.1MP Image Sensor
- 1080p(1920x1080)@30fps/25fps
- 20m IR Distance
- Fixed Lens 3.6mm

IR Indoor Dome



STD-A2M30IRV

- Sony Exmor 2.1MP Image Sensor
- 1080p(1920x1080)@30fps/25fps
- 30m IR Distance
- Motorized 2.8~12mm VF Mega Lens

IR Outdoor Vandal Dome



STV-A2M32IRV

- Sony Exmor 2.1MP Image Sensor
- 1080p(1920x1080)@30fps/25fps
- 30m IR Distance
- Motorized 2.8~12mm VF Mega Lens
- IP66 Weatherproof

Bullet



STU-B2M24IR

- Sony Exmor 2.1MP Image Sensor
- 1080p(1920x1080)@30fps/25fps
- 20m IR Distance
- Fixed Lens 3.6mm(3MP)
- IP68 Waterproof

Bullet



STU-A2M35IR

- Sony Exmor 2.1MP Image Sensor
- 1080p(1920x1080)@30fps/25fps
- 35m IR Distance
- Fixed Lens 3.6mm(3MP)
- IP68 Waterproof

Bullet



STU-A2M72IR

- Sony Exmor 2.1MP Image Sensor
- 1080p(1920x1080)@30fps/25fps
- 70m IR Distance
- Fixed Lens 6mm(3MP)
- IP68 Waterproof

Bullet



STU-A2M42IRV

- Sony Exmor 2.1MP Image Sensor
- 1080p(1920x1080)@30fps/25fps
- 40m IR Distance
- Motorized 2.8~12mm VF Mega Lens
- IP68 Waterproof

Bullet



STU-B2M42IRV

- Sony Exmor 2.1MP Image Sensor
- 1080p(1920x1080)@30fps/25fps
- 40m IR Distance
- Motorized 2.8~12mm VF Mega Lens
- IP68 Waterproof

Bullet



STU-A2M60IRV

- Sony Exmor 2.1MP Image Sensor
- 1080p(1920x1080)@30fps/25fps
- 60m IR Distance
- Motorized 2.8~12mm VF Mega Lens (6~50mm ICR VF Lens Available)
- IP68 Waterproof

IR Housing



STH-B2M84IR(V)

- Sony Exmor 2.1MP Image Sensor
- 1080p(1920x1080)@30fps/25fps
- 80m IR Distance
- Motorized 2.8~12mm VF Mega Lens (Fixed Lens/6~50mm VF Lens Available)
- IP66 Weatherproof

IR Housing



STH-A2M84IR(V)

- Sony Exmor 2.1MP Image Sensor
- 1080p(1920x1080)@30fps/25fps
- 80m IR Distance
- Motorized 2.8~12mm VF Mega Lens (Fixed Lens/6~50mm VF Lens Available)
- IP66 Weatherproof

10X Zoom Bullet



STU-A2M60IR/Z10

- Sony Exmor 2.1MP Image Sensor
- 1080p(1920x1080)@30fps/25fps
- 60m IR Distance
- Optical 10x Zoom 5~50mm VF Lens
- IP68 Weatherproof

IR Indoor Dome



SAD-2A24IR

- Sony Exmor 2.1MP Image Sensor
- 1080p(1920x1080)@30fps/25fps
- 20m IR Distance
- Fixed Lens 3.6mm(3MP)

IR Indoor Dome



SAD-2A30IRV

- Sony Exmor 2.1MP Image Sensor
- 1080p(1920x1080)@30fps/25fps
- 30m IR Distance
- Motorized 2.8~12mm VF Mega Lens

IR Outdoor Vandal Dome



SAV-2A32IRV

- Sony Exmor 2.1MP Image Sensor
- 1080p(1920x1080)@30fps/25fps
- 30m IR Distance
- Motorized 2.8~12mm VF Mega Lens
- IP66 Weatherproof

Miniature



SAS-2A32

- Sony Exmor 2.1MP Image Sensor
- 1080p(1920x1080)@30fps/25fps
- Fixed Lens 3.6mm (Pinhole Lens available)

Bullet



SAU-2B24IR

- Sony Exmor 2.1MP Image Sensor
- 1080p(1920x1080)@30fps/25fps
- 20m IR Distance
- Fixed Lens 3.6mm(3MP)
- IP68 Waterproof

Bullet



SAU-2A35IR

- Sony Exmor 2.1MP Image Sensor
- 1080p(1920x1080)@30fps/25fps
- 35m IR Distance
- Fixed Lens 3.6mm(3MP)
- IP68 Waterproof

Bullet



SAU-2A72IR

- Sony Exmor 2.1MP Image Sensor
- 1080p(1920x1080)@30fps/25fps
- 70m IR Distance
- Fixed Lens 6mm(3MP)
- IP68 Waterproof

Bullet



SAU-2A42IRV

- Sony Exmor 2.1MP Image Sensor
- 1080p(1920x1080)@30fps/25fps
- 40m IR Distance
- Motorized 2.8~12mm VF Mega Lens
- IP68 Waterproof

Bullet



SAU-2B42IRV

- Sony Exmor 2.1MP Image Sensor
- 1080p(1920x1080)@30fps/25fps
- 40m IR Distance
- Motorized 2.8~12mm VF Mega Lens
- IP68 Waterproof

Bullet



SAU-2A60IRV

- Sony Exmor 2.1MP Image Sensor
- 1080p(1920x1080)@30fps/25fps
- 60m IR Distance
- Motorized 2.8~12mm VF Mega Lens (6~50mm ICR VF Lens Available)
- IP68 Waterproof

IR Housing



SAH-2B84IR(V)

- Sony Exmor 2.1MP Image Sensor
- 1080p(1920x1080)@30fps/25fps
- 80m IR Distance
- Motorized 2.8~12mm VF Mega Lens (Fixed Lens/6~50mm VF Lens Available)
- IP66 Weatherproof

IR Housing



SAH-2A84IR(V)

- Sony Exmor 2.1MP Image Sensor
- 1080p(1920x1080)@30fps/25fps
- 80m IR Distance
- Motorized 2.8~12mm VF Mega Lens (Fixed Lens/6~50mm VF Lens Available)
- IP66 Weatherproof

DVR

SECUS

Premium Hybrid AHD DVR



HVR-NAS04/08/16

- 960H & AHD 2.0 Hybrid DVR with UTC
- Real Time Recording@1080p
- Up to 4HDD(16TB)
- P2P support

Advantage Hybrid AHD DVR



HVR-NAL04/08/16

- 960H & AHD 2.0 Hybrid DVR with UTC
- 15fps/ch@1080p
- Up to 2HDD(8TB)
- P2P support

Low-end Hybrid AHD DVR



HVR-NAR04/08

- 960H & AHD 2.0 Hybrid DVR with UTC
- 15fps/ch@1080p
- Up to 1HDD(3TB)
- P2P support

Premium HD-TVI DVR



HVR-RTH04/08/16

- 960H & TVI & IP
- Real Time Recording@1080p
- Up to 4HDD(16TB) + 1 e-SATA
- P2P support

Advantage HD-TVI DVR



HVR-RTL04/08/16

- 960H & TVI Hybrid DVR
- 12fps/ch@1080p
- Up to 2HDD(8TB)
- P2P support
- Hybrid DVR

AHD Combo DVR



HVR-ECA04

- 960H & AHD 2.0 Hybrid DVR
- 10" folding LCD in-built
- Up to 1HDD(4TB)
- Connection with POS equipment

PTZ

SECUS

Hybrid TVI/AHD PTZ



HPT-TA100W

- Panasonic 2.1MP Image Sensor
- TVI & AHD Hybrid Speed Dome
- 5.1~51mm Vari-Focal Lens
- Optical Zoom 10x/Digital Zoom 32x

Hybrid TVI/AHD PTZ



HPT-TA20(30)OW

- Sony Exmor 2.1MP Image Sensor
- TVI & AHD Hybrid Speed Dome
- 4.45~89mm Vari-Focal Lens
- Optical Zoom 20x/Digital Zoom 16x

Hybrid TVI/AHD PTZ



HPT-H5230IRO

- Sony Exmor 2.1MP Image Sensor
- TVI & AHD Hybrid Speed Dome
- 150m IR distance
- 4.3~129mm Vari-Focal Lens
- Optical Zoom 30x/Digital Zoom 20x

2MP Mini PTZ



HIP-SZ255(Mini IP PTZ)

- Sony Exmor 2.1MP Image Sensor
- 5.1~51mm Vari-Focal Lens
- Optical Zoom 10x/Digital Zoom 32x
- 30fps@1080p
- Support PoE/Onvif

2MP IP PTZ



HIP-SZ249

- 2.1MP Image Sensor
- 4.7~94mm Vari-Focal Lens
- Optical Zoom 20x/Digital Zoom 32x
- 30fps@1080p
- Support PoE/Onvif

2MP IR IP PTZ



HIP-SZ249IR

- 2.1MP Image Sensor
- 4.7~94mm Vari-Focal Lens
- Optical Zoom 20x/Digital Zoom 32x
- 100m IR distance
- 30fps@1080p
- Support PoE/Onvif

Thermal Imaging IP Network Camera



HTS-600N

- Advanced Thermal IP Camera
- 640x480 resolution
- 8-14μm(Long-wave IR)
- Fixed/Manual/Motorized Lens
- Onvif support

Pan/Tilt Driver



HTS-PTD(Mid-Range)

- Robust and Efficient Pan/Tilt
- Pan Speed : 0.025°~60°/sec
- Tilt Speed : 0.025°~25°/sec
- Pan angle : 360° endless
- Tilt angle : -70°~+25° • IP66

Wearable Camera



HWC-V01

- Mini-USB Bullet Camera
- 640x480, 1280x720
- USB On-The-Go(USB 2.0)
- Micro USB 5 Pin
- Fixed 3.6mm

Smartphone-AHD Rapport



HA-CSA02

- Smartphone-AHD(USB 3.0)
- Video input: AHD 1.0 & 2.0
- Video output: WiFi
- Resolution : 1920x1080/30pfs
- Power : Smartphone Power

Multi Test Monitor



HMT-SEH07

- 7" TFT-LCD(LED back light)
- HD-SDI, EX-SDI, HDMI, VGA, CVBS AHD, HD-TVI, HD-CVI input
- PTZ control(RS-485)
- Coaxial Communication

Multi WiFi Rapport



HMW-CA05

- WiFi Rapport
- HD-SDI, HDMI, VGA, CVBS, AHD, HD-TVI input
- Connect with Smartphone & Tablet PC
- Fixed 3.6mm

+hanse ENGINEERING

SECUS

42B-2L, 629-1, Namchon-dong, Namdong-gu, Incheon, 405-400, Korea

T. +82-32-814-8784 F. +82-32-812-8784 E-mail: sales@secus.co.kr

Website: www.secus.co.kr

