



## 4MEGAPIXEL ANALOG HD ALL-IN-ONE CAMERA

# SAD-4AM24IRV



### DIMENSION



### FEATURES

- 1/3", 4 MegaPixel CMOS
- ALL IN ONE (AHD/TVI/CVBS) Video Output
- True Day & Night
- NTSC/PAL Selectable
- 3-Axis Gimbal Bracket
- IR LED 24pcs
- VariFocal LENS 2.8~12mm (Manual Lens)
- Option : OSD Controller

### SPECIFICATIONS

| SAD-4AM24IRV          |                                                            |
|-----------------------|------------------------------------------------------------|
| Signal Format         | NTSC   PAL                                                 |
| Image Sensor          | 1/3", 4 MegaPixel CMOS                                     |
| Effective Pixels      | 2688(H) × 1520(V)                                          |
| Video Output          | AHD/TVI/CVBS                                               |
| Mini. Illumination    | 0.01LUX                                                    |
| S/N ratio             | More Than 50dB                                             |
| Electronic Shutter    | AUTO (PAL : 1/50-1/50, 000Sec<br>NTSC : 1/60-1/50, 000Sec) |
| Day & Night           | External(default) / Auto / Color / BW(OSD Switch)          |
| White balance         | AUTO                                                       |
| BLC                   | AUTO                                                       |
| HLC/2D                | SUPPORT                                                    |
| Language              | English / Chinese / Japanese                               |
| LENS                  | VariFocal LENS 2.8~12mm (Manual Lens)                      |
| Power Supply          | DC 12V ±10%                                                |
| Power Consumption     | LED OFF : Max. 1.8W   LED ON : Max. 2.8W                   |
| Operating Temperature | -10°C ~ +50°C                                              |
| Operating Humidity    | Less than 90%                                              |
| Dimension             | 112.6(Ø) x 89.4(H)mm                                       |
| Weight                | Approx. 320g                                               |

\* In accordance with customers' request and OSD controller's option, the specifications can be fixed or changed without notice.