




1080p / 3D-DNR / WDR
2.1M PIXEL SQUARE CAMERA

SDI-SJ212

FEATURES

- 1/3" 2.1Megapixel Progressive Panasonic CMOS
- 1080p(1920x1080)@30fps
- Min. Illumination of 0.001Lux(Sense-up x8)
- Day & Night
- NTSC/PAL selectable
- Defog(Visibility enhancement on the low contrast scene)
- High resolution digital zoom (x8)
- 2D & 3D Digital Noise Reduction
- Flicker Suppression
- Motion Detection, Privacy Masking (16 Zone)
- 3-Axis Gimbal Bracket
- Option : RS-485 / OSD Controller / Dual Voltage (DC 12V / AC 24V)

DIMENSION



SPECIFICATIONS

SDI-SJ212	
Signal Format	NTSC/PAL (Selectable)
Image Sensor	1/3" 2.1Megapixel Panasonic CMOS
Effective Pixels	1944(H) x 1092(V) = 2,122,848 (Pixel)
Scanning System	Progressive Scan
Video Output Mode	1080p(1920 x 1080)@30fps
Video Output Level	HD-SDI / CVBS : 1.0Vp-p / 75 (W/O WDR)
Min. Illumination	0.5Lux(Color), 0.1Lux(B&W), 0.001Lux(Sens-up x8)
Electronic Shutter Speed	NTSC : 1/30 ~ 1/60,000sec, PAL : 1/25 ~ 1/50,000sec
Iris Control	SELECTA
S/N Ratio	More 50dB
Backlight Compensation	OFF / HLC / BLC / WDR
White Balance	AUTO / AUTOEXT / PRESET / MANUAL
Gain Control	0~20
2D + 3D DNR	OFF / LOW / MIDDLE / HIGH
Day & Night	AUTO / B.W / COLOR / EXT
Sense-up	x2 ~ x8
D-WDR	OFF / ON
Digital Zoom	x1.0~ x8.0
Flickerless	OFF / ON
Motion Detection	ON / OFF
Privacy Masking	ON / OFF (16 ZOOM)
Defog	OFF / ON
D - EFFECT	MIRROR / D-ZOOM / FLIP
OSD	Eng / Jpn / Chi
Lens	Fixed Lens 3.6mm / Pin Hole Lens 4.3mm
Power Supply	DC 12V (±10%)
Power Consumption	Max. 2.5W
Operating Temperature	-10°C ~ +50°C
Operating Humidity	Less than 90%
Dimension	38.6(W) x 37.0(H) x 22.3(D)mm
Weight	Approx. 60g

* In accordance with customers' request and OSD controller's option, the specifications can be fixed or changed without notice.